




APP Tools


for EXPERT 10.6 Rework Systems






SF64.0520 Print Tool with squeegee





SF64.0525, SF64.0526, SF64.0527 Dip Tool 32 x 0,08 mm with squeegee Dip Tool 32 x 0,15 mm with squeegee Dip Tool 32 x 0,22 mm with squeegee



SF64.0540 μSMD Tool

A variety of application tools are available to enable rework of delicate electronic devices. Providing increased automation while simplifying operator requirements results in higher yields and increased process repeatability. Combined with the EXPERT's AVP (Automated Vision Placement) system, innovative application tools reduce overall process times and increase throughput.

<u>Print Tool:</u> This tool is designed to enable QFN and other delicate SMD rework. Using a stencil type fixture, solder paste or paste flux can be applied directly to a component's interconnects. Once printed, an operator secures the Print Tool housing the printed component to the EXPERT's Process Shuttle. The AVP picks a printed component from the pre-positioned Print Tool and aligns the component to prepared pads of the rework site, hands free. Reworking a QFN with the Print Tool becomes similar to typical BGAs.

<u>Dip Tool:</u> The application of solder flux or solder paste is simplified using the Dip-Tool. A defined quantity of flux or solder paste is precisely applied to the component by the system. The SMD is loaded onto a Component Nest supported by the Process Shuttle. Once picked by the system, the component is then dipped into and removed from the Dip Tool, aligned and then placed by AVP to prepared pads of the rework site, hands free.

 $\underline{\mu SMD\ Tool:}$ Even the smallest SMD component is now able to be handled with the EXPERT 10.6 rework system when using the μSMD Nest. Loading of small components can even be done off-line. The pre-loaded μSMD Nest is then installed onto the Process Shuttle awaiting pick-up by the system.

Feature Availability

 Application Tools may require component specific tooling such as sliders, masks and frames. Standard tooling is readily available from MARTIN. Also available is custom tooling to meet your rework needs.



Technical Data

Print Tool (size range Dip Tool (size range BGA) μSMD Tool (size range) 1,5 x 1,5 mm² - 20 x 120 mm² 3 x 3 mm² - 27 x 27 mm² 0402 – 5 x 5 mm²

APP Tools - for EXPERT 10.6 Rework Systems

Options and Accessories – PRINT TOOL

SF64.0520	Print tool with squeegee	
	for tool slider	
SF64.0501	Tool slider	
	for AVP 4.1	
•		
SF66.0501	Tool slider	
	for AVP 4.1XL	
Í		
LWxx.xx11	Prebumping mask+frame QFN	Maske nach Wahl
	Type of standard QFN mask on request	_ warn
İ		9 38um
VD90.0230	Solder paste print 5ccm finepitch 4 lead free	5 ccm Lead free
	Sn96.5Ag3Cu, ROL0 / 20-38μm	_
Í		
LW10.0004	Solder paste squeegee	
	for QFN Printer	

Options and Accessories - DIPP TOOL

•		
SF64.0525	Dip tool 32x0.08mm with squeegee	
	for tool slider	
1		
SF64.0526	Dip tool 32x0.15mm with squeegee	
	for tool slider	
1		
SF64.0527	Dip tool 32x0.22mm with squeegee	
	for tool slider	
Ì		F
SF64.0501	Tool slider	
	for AVP 4.1	
Ì		F. [
SF66.0501	Tool slider	7
	for AVP 4.1XL	
Í		
HT00.0116	Flux Creme lead free 5ccm	Lead free
	(appr. 5g), 0506 MA, no clean, REL0	_ &_
ı		100g
HT00.0117	Flux Creme lead free 100g	Flux-Creme Leadfree
	0506 MA, no clean, REL0	leadfree
1		NI
LW10.0005	Squeegee	
	for dipp tool	

Options and Accessories – µSMD TOOL

SF64.0540	μSMD tool for tool slider	
SF64.0501	Tool slider for AVP 4.1	
SF66.0501	Tool slider for AVP 4.1XL	

Further units and consumables under www.martin-smt.de