

## Extraction Arm Nozzles












[www.linkhamson.com](http://www.linkhamson.com)

Tel: +44 (0)1494 439786

[sales@linkhamson.com](mailto:sales@linkhamson.com)



Order No.	Description	
ALFA	<b>Easy-Click-60 funnel nozzle</b> 225 mm x 100 mm	 ESD safe
ALFA-T	<b>Easy-Click-60 transparent funnel nozzle</b>	
	<b>Easy-Click-60 metal sloped nozzle</b> Ø 50 mm, length 130 mm	 ESD safe
FT-NL	<b>Easy-Click-60 metal sloped nozzle</b> Ø 60 mm, length 130 mm	 ESD safe
FT-NS	<b>Easy-Click-60 metal tube nozzle, sloped with grid</b> Ø 50 mm, length 130 mm	 ESD safe
FT-P	<b>Metal tube nozzle sloped</b> for aluminium arms, length adjustable (105–235 mm), Ø 50 mm	 ESD safe
T005 87 628 34	<b>Metal sloped nozzle 32</b> for 32 mm flex arms, Ø 31 mm, length 100 mm	 ESD safe
FT-U	<b>Easy-Click-60 nozzle</b> width 190 mm, length 100 mm	 ESD safe
T005 87 358 45	<b>Metal exhaust hood</b> 200 x 100 mm (7.87 x 3.93 in), recommended for use with hot air soldering operations incl. adapter T005 87 627 53	 ESD safe
Z	<b>Adapter</b> to mount nozzles on aluminium arm with possibility to turn the nozzle	 ESD safe