



Link Hamson Ltd
22A Kingfisher Court, Hambridge Road
Newbury, Berkshire RG14 5SJ

RHT40 Durable Resin Based Ribbon

Specific Features:

- Resin ribbon for excellent barcodes and variable images.
- Excellent heat resistance.
- Good solvent resistance.
- Good scratch resistance.
- High density.
- Highly versatile: compatible with a vast array of substrates.



Recommended Applications:

- Shelf labels, warning labels, drums labels, **component labels**, demanding automotive labels and under hood labels, pharmaceutical labels, **circuit board labelling**, outdoor use.
- In general, applications where scratch resistance, rub resistance, solvent and heat resistance are important.

Substrates:

Polyesters, PVC, Polyimides & synthetic labels.

Item	Value	Test method
Colour	Black	-
Polyester Film Thickness	4.5 microns +/-0.4	Micrometre
Total Thickness	9.0 ± 0.8	Micrometre
Shelf-Life	TWO Years	@ 21°C / 50% RH

Part Nos:

LP5119, LP5119/7

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Link Hamson makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Link Hamsons only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will Link Hamson be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Link Hamson Specifications are subject to change without notice. In addition Link Hamson reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.

RHT40_03_21